



STATIKIL PE

Topical anti-stat formulated for PE gas piping

Excellent visibility on all PE pipes



Product available ready for use in:

- 32 oz spray bottle with simple trigger spray for accurate application.
- 1 Gallon containers




ProReach128 (one gallon) long reach sprayer accessory available for above ditch applications

- Effectively eliminates static charges on PE gas pipe by increasing surface conductivity
- Eliminates need for bulky burlap or pipe wraps
- Keeps work area clear and eliminates trip hazards posed by other grounded pipe “wraps”
- To be used prior to construction operations including squeeze-off, repair, tapping, cutting, venting, etc.
- Colorant added for positive verification of product coverage
- Remains effective even after pipe is dry
- No aerosols. No wasted over spray.

Specifications

Composition	High Molecular Weight Topical Antistat
Physical Form	Liquid
Color	Gray Pigment for Visibility
Flash Point	None
Freeze Point	-10° F
Explosion Hazard	None
Specific Gravity	1.0
Odor	Mild Lemon
pH Regular	7.71
Static Decay Rate	MIL-B-81705-B At Relative Humidity @13% 72°F .35 Sec @5 KV

STATIKIL PE has been tested by independent laboratories and meets or exceeds ASTM D-257-80, MIL B-81705-B, Electronic Industry IS-5 and NFPA-99 specifications for surface resistivity and static decay.



PLEASE VISIT WWW.STATIKILPE.COM TO SEE A VIDEO OF STATIKIL PE IN ACTION!

Distributed by:



GROEBNER
POWERED BY EXPERIENCE

For training, sales & service, contact us:
800-638-8322
www.groebner.com

MANUFACTURED BY

Pipeline Equipment Resources Company, LLC

www.perc.us.com